

# 200G QSFP56 HDR to 2x100G QSFP56 HDR100 Breakout Passive Direct Attach Copper Cable

## Features

- IBTA InfiniBand HDR compliant
- 200Gb/s HDR to 2x100Gb/s HDR100 data rate
- 4x 50Gb/s PAM4 modulation
- SFF-8665 compliant
- Operating case temperature 0-70°C
- Single 3.3V supply voltage
- BER (Bit Error Rate) 1E-15 with InfiniBand systems
- Hot pluggable
- RoHS compliant
- PVC jacket
- LF (Lead Free) HF (Halogen Free) PCB
- SFF-8636 compliant I<sup>2</sup>C management interface

## Description

The Q2Q56-200G-DACH splitter cables are high-speed, cost-effective alternatives to fiber optics in 200Gb/s InfiniBand HDR applications.

Q2Q56-200G-DACH cables provide connectivity between system units with a 200Gb/s HDR QSFP56 port on one side and two 100Gb/s HDR100 QSFP56 ports on the other side. The cable connects the data signals from each of the 2 dual copper pairs on the single QSFP56 (pair 1&2, 3&4) end to the dual copper pair of each of the QSFP56 (pair 1&2) ends on the multi-port side. Each QSFP56 port comprises an EEPROM providing product information, which can be read by the host system.

NADDOD's unique quality passive copper cable solutions provide power-efficient connectivity for short distance interconnects. It enables higher port bandwidth, density and configurability at a low cost and reduced power requirement in the data centers.

Rigorous cable production testing ensures best out-of-the box installation experience, performance and durability.

## Absolute Maximum Ratings

Table1-Absolute Maximum Ratings					
Parameter	Min.	Typical	Max.	Unit	Note
Storage Temperature	-40	-	+85	°C	
Supply voltage	-0.3	-	3.6	V	
Data input voltage	-0.3	-	3.6	V	
Control input voltage	-0.3	-	3.6	V	

## Operational Specifications

Table2-Operational Specifications					
Parameter	Min.	Typical	Max.	Unit	Note
Supply voltage (Vcc)	3.135	3.3	3.465	V	
Power consumption	-	-	0.1	W	
Operating case temperature	0	-	70	°C	
Operating relative humidity	5	-	85	%	

## Electrical Specifications

Table3-Electrical Specifications					
Parameter	Min.	Typical	Max.	Unit	Note
Characteristic impedance	90	100	110	Ω	
Time propagation delay (informative)	-	-	4.5	ns/m	



## Part Numbers and Descriptions

**Table5-Part Numbers and Descriptions**

Part Number	Description
Q2Q56-200G-CU1H	passive copper hybrid cable, IB HDR 200Gb/s to 2x100Gb/s, QSFP56 to 2xQSFP56, PVC, colored, 1m, 30AWG
Q2Q56-200G-CU1-5H	passive copper hybrid cable, IB HDR 200Gb/s to 2x100Gb/s, QSFP56 to 2xQSFP56, PVC, colored, 1.5m, 30AWG
Q2Q56-200G-CU2H	passive copper hybrid cable, IB HDR 200Gb/s to 2x100Gb/s, QSFP56 to 2xQSFP56,PVC, colored, 2m, 30AWG
Q2Q56-200G-CU2-5H	passive copper hybrid cable, IB HDR 200Gb/s to 2x100Gb/s, QSFP56 to 2xQSFP56, PVC, colored, 2m, 26AWG
Q2Q56-200G-CU3H	passive copper hybrid cable, IB HDR 200Gb/s to 2x100Gb/s, QSFP56 to 2xQSFP56, PVC, colored, 3m, 26AWG

## Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation

## Further Information:

---

Web [www.naddod.com](http://www.naddod.com)

Email For order requirements: [sales@naddod.com](mailto:sales@naddod.com)  
For customer service: [support@naddod.com](mailto:support@naddod.com)  
For technical support: [tech@naddod.com](mailto:tech@naddod.com)

For cooperation: [agency@naddod.com](mailto:agency@naddod.com)

For other informations: [info@naddod.com](mailto:info@naddod.com)

## Disclaimer

---

1. We are committed to continuous product improvement and feature upgrades, and the contents contained in this manual are subject to change without notice.
2. Nothing herein should be construed as constituting an additional warranty.
3. NADDOD assumes no responsibility for the use or reliability of equipment or software not provided by NADDOD.

Copyright © NADDOD.COM All Rights